

(12) UK Patent Application (19) GB (11) 2 366 143 (13) A

(43) Date of A Publication 27.02.2002

(21) Application No 0104709.1

(22) Date of Filing 26.02.2001

(30) Priority Data

(31) 12047664

(32) 24.02.2000

(33) JP

(71) Applicant(s)

NEC Corporation

(Incorporated in Japan)

7-1, Shiba 5-chome, Minato-ku, Tokyo 108-8001,
Japan

(72) Inventor(s)

Hidetoshi Takenaka

(74) Agent and/or Address for Service

Reddie & Grose

16 Theobalds Road, LONDON, WC1X 8PL,
United Kingdom

(51) INT CL⁷

H04Q 7/32

(52) UK CL (Edition T)

H4L LERA

(56) Documents Cited

GB 2333205 A

GB 2284693 A

GB 2253541 A

(58) Field of Search

UK CL (Edition S) G4H HRCU, H4K KBHC, H4L LECCP

LECCX LERA LERX

INT CL⁷ H04M 1/725 11/04, H04Q 7/32

ONLINE: WPI, EPODOC, JAPIO, INSPEC


(54) Abstract Title

Ringling of mobile until acknowledgement


(57) A portable telephone, alerts the user of call reception, and creates a record of reception. If no response is made to the initial notification, an alarm is generated until the history of reception is confirmed. If a user misses the original alert - for example a silent ringing (LED, light alert) then he may be reminded of the call later by repetition of the alert or a different alarm - perhaps audible or vibrating alert. The notification may only be intermittently repeated for previously designated numbers stored in the memory.

FIG. 4


(a)



(b)



(c)



Best Available Copy

GB 2 366 143 A

FIG. 1 PRIOR ART




FIG. 2




FIG. 3






FIG. 4

4/6

(a)



(b)



(c)




FIG. 5

5/6





FIG. 6



PORTABLE TELEPHONE

FIELD OF THE INVENTION

5 The present invention relates to a portable telephone having a function of recording the history of reception.

BACKGROUND OF THE INVENTION

Nowadays, many types of portable telephones are provided with
10 a function of recording the history of reception. In these types of portable telephones, in the case no response to a phone call is made and the history of the reception of the phone call has been recorded, on an LCD display part there is displayed information such as, for example, a "someone called you". Thereby, the user is informed of
15 that a call was received.

Fig. 1 is a flow chart illustrating the operation at the time of a reception of a known portable telephone.

When a call from someone is received (step S61), the history of reception is recorded (step S62), and thereupon it is determined
20 whether there is a response to the call (step S63).

In the case it is determined in step S63 that there is a response, a phone talk between the user and the calling person is made (step S68). When the phone talk is ended (step S69), on the LCD display part there is displayed an ordinary standby window (step S67).

25 On the other hand, in the case it is determined in step S63 that there is no response, on the LCD display part there is displayed information of, for example, "someone called you" (step S64). Subsequently, it is determined whether the history of the received call is confirmed (step S65).

30 In the case it is determined in step S65 that the history of

the received call is confirmed, the information of "someone called you" displayed on the LCD display part is erased (step S66). Thereafter, the ordinary-standby window is displayed on the LCD displayed part (step S67).

5 On the other hand, in the case it is determined in step S65 that the history of the received call is not confirmed, the flow returns again to the processing of step S65, and then the confirmation of the history of the received call is conducted.

 However, a portable telephone is one that is usually carried
10 by the user while being put in the user's bag or pocket. Therefore, there is a case where the user does not become aware of the reception sound by reason of the surrounding noises or the like. In such a case, even when in a later piece of processing the information of "someone called you" has been displayed on the LCD display part, there is the
15 following possibility. Namely, the information on the window is left as it stands for a large length of time until the user looks at this window of the LCD display part.

 Especially, in a folding type portable telephone that is carried in a state of its being folded up, in order for the user to look at
20 the window of the LCD display part it is necessary to open the portable telephone. For this reason, the probability that the information of the window will be left as is until the next day becomes high.

SUMMARY OF THE INVENTION

According to the present invention there is provided a portable telephone in which the informing of a reception is

performed at the time of the reception by causing a buzzer to generate its reception sound and simultaneously a history of the reception is recorded in a memory, wherein

in the case no response to the informing of the reception is
5 made and the history of the reception is recorded in the memory, the buzzer generates an alarming sound until the history of the reception is confirmed.

The buzzer may generate its alarming sound for a prescribed time length in units of a prescribed time length until the history
10 of the reception is confirmed.

Preferably, the memory records therein a telephone number that is designated beforehand, and

the buzzer generates its alarming sound until the history of the reception is confirmed only in the case a telephone number of
15 the reception coincides with the previously designated telephone number that is recorded in the memory.

Also, the invention provides

a portable telephone in which the informing of a reception is performed at the time of the reception by causing an LED to turn "on"
20 / "off" and simultaneously a history of the reception is recorded in a memory, wherein

in the case no response to the informing of the reception is made and the history of the reception is recorded in the memory, the LED turns "on" / "off" until the history of the reception is confirmed.

25 The LED may turn "on" / "off" for a prescribed time length in units of a prescribed time length until the history of the reception is confirmed.

Preferably, the memory records therein a telephone number that is designated beforehand, and

30 the LED turns "on" / "off" until the history of the reception

is confirmed only in the case the telephone number of the reception coincides with the previously designated telephone number that is recorded in the memory.

Also, the invention provides

5 a portable telephone in which the informing of a reception is performed at the time of the reception by causing a vibrator to vibrate and simultaneously a history of the reception is recorded in a memory, wherein

10 in the case no response to the informing of the reception is made and the history of the reception is recorded in the memory, the vibrator vibrates until the history of the reception is confirmed.

The vibrator may vibrate for a prescribed time length in units of a prescribed time length until the history of the reception is confirmed.

15 Preferably, the memory records therein a telephone number that is designated beforehand; and

the vibrator vibrates until the history of the reception is confirmed only in the case the telephone number of the reception coincides with the previously designated telephone number that is
20 recorded in the memory.

Also, a portable telephone in which the informing of a reception is performed at the time of the reception by causing a buzzer to generate its alarming sound and causing an LED to turn "on" / "off" and simultaneously a history of the reception is recorded in a memory,
25 wherein

in the case no response to the informing of the reception is made and the history of the reception is recorded in the memory, the buzzer generates its alarming sound until the history of the reception is confirmed, and

30 in the case no response to the informing of the reception is

made and the history of the reception is recorded in the memory, the LED turns "on" / "off" until the history of the reception is confirmed.

Preferably the buzzer generates its alarming sound for a prescribed time length in units of a prescribed time length until
5 the history of the reception is confirmed, and

the LED turns "on" / "off" for a prescribed time length in units of a prescribed time length until the history of the reception is confirmed.

Preferably, the memory records therein a telephone number
10 that is designated beforehand, and

the buzzer generates its alarming sound until the history of the reception is confirmed only in the case the telephone number of the reception coincides with the previously designated telephone number that is recorded in the memory, and

15 the LED turns "on" / "off" until the history of the reception is confirmed only in the case the telephone number of the reception coincides with the previously designated telephone number that is recorded in the memory.

Also, the invention provides a portable telephone in which the
20 informing of a reception is performed at the time of the reception by causing a buzzer to generate its alarming sound and causing a vibrator to vibrate and simultaneously a history of the reception is recorded in a memory, wherein

in the case no response to the informing of the reception is
25 made and the history of the reception is recorded in the memory, the buzzer generates its alarming sound until the history of the reception is confirmed, and

in the case no response to the informing of the reception is made and the history of the reception is recorded in the memory, the
30 vibrator vibrates until the history of the reception is confirmed.

Preferably, the buzzer generates its alarming sound for a prescribed time length in units of a prescribed time length until the history of the reception is confirmed, and

the vibrator vibrates for a prescribed time length in units of a prescribed time length until the history of the reception is confirmed.

Preferably, the memory records therein a telephone number that is designated beforehand.

the buzzer generates its alarming sound until the history of the reception is confirmed only in the case the telephone number of the reception coincides with the previously designated telephone number that is recorded in the memory, and

the vibrator vibrates until the history of the reception is confirmed only in the case the telephone number of the reception coincides with the previously designated telephone number that is recorded in the memory.

Also, the invention provides a portable telephone in which the informing of a reception is performed at the time of the reception by causing an LED to turn "on" / "off" and causing a vibrator to vibrate and simultaneously a history of the reception is recorded in a memory, wherein

in the case no response to the informing of the reception is made and the history of the reception is recorded in the memory, the LED turns "on" / "off" until the history of the reception is confirmed, and

in the case no response to the informing of the reception is made and the history of the reception is recorded in the memory, the vibrator vibrates until the history of the reception is confirmed.

Preferably, the LED turns "on" / "off" for a prescribed time length in units of a prescribed time length until the history of the reception is confirmed, and

the vibrator vibrates for a prescribed time length in units of a prescribed time length until the history of the reception is confirmed.

Preferably, the memory records therein a telephone number that is designated beforehand.

5 the LED turns "on" / "off" until the history of the reception is confirmed only in the case the telephone number of the reception coincides with the previously designated telephone number that is recorded in the memory, and

the vibrator vibrates until the history of the reception is confirmed only in the case the telephone number of the reception coincides with the previously designated telephone number that is recorded in the memory.

Also, the invention provides a portable telephone in which the informing of a reception is performed at the time of the reception by causing an LED to turn "on" / "off" and causing a vibrator to vibrate and simultaneously a history of the reception is recorded in a memory, the portable telephone comprising

a buzzer that at the time of a reception informs the reception by generating a reception sound and that, in the case no response to the informing of the reception is made and the history of the reception is recorded in the memory, generates its alarming sound until the history of the reception is confirmed, wherein

in the case no response to the informing of the reception is made and the history of the reception is recorded in the memory, the LED turns "on" / "off" until the history of the reception is confirmed, and

in the case no response to the informing of the reception is made and the history of the reception is recorded in the memory, the vibrator vibrates until the history of the reception is confirmed.

30 The buzzer may generate its alarming sound for a prescribed

time length in units of a prescribed time length until the history of the reception is confirmed.

Preferably the LED turns "on" / "off" for a prescribed time length in units of a prescribed time length until the
5 history of the reception is confirmed, and

the vibrator vibrates for a prescribed time length in units of a prescribed time length until the history of the reception is confirmed.

Preferably, the memory records therein a telephone number that is designated beforehand.

10 the buzzer generates its alarming sound until the history of the reception is confirmed only in the case the telephone number of the reception coincides with the previously designated telephone number that is recorded in the memory,

the LED turns "on" / "off" until the history of the reception
15 is confirmed only in the case the telephone number of the reception coincides with the previously designated telephone number that is recorded in the memory; and

the vibrator vibrates until the history of the reception is confirmed only in the case the telephone number of the reception
20 coincides with the previously designated telephone number that is recorded in the memory.

In an embodiment of the present invention that is constructed as stated above in the case no response to the informing of the reception is made and the history of the reception is recorded, one or more of the alarming
25 sound generation operation, the vibrator vibration operation, and the LED "on" / "off" operation are performed until the history of the reception is confirmed.

As a result of this, the user is urged to confirm the history of the reception. Therefore, the fact that a call has been received
30 is informed to the user earlier.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a flow chart illustrating an example of the operation at the time of reception of a known portable telephone;

5 Fig. 2 is a view illustrating an embodiment of a portable telephone according to the present invention;

Fig. 3 is an outer appearance view of the portable telephone illustrated in Fig. 2;

10 Figs. 4(a), 4(b), and 4(c) each are a view illustrating information displayed on an LCD display part illustrated in Fig. 2;

Fig. 5 is a flow chart illustrating an example of the operation at the time of reception of the portable telephone illustrated in Fig. 2; and

15 Fig. 6 is a flow chart illustrating another example of the operation at the time of reception of the portable telephone illustrated in Fig. 2.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

20 An embodiment of the present invention will hereafter be explained with reference to the drawings.

Fig. 2 is a view illustrating an embodiment of a portable telephone according to the present invention. Fig. 3 is an outer appearance view of the portable telephone illustrated in Fig. 2 and shows a collapsible portable telephone.

25 As illustrated in Figs. 2 and 3, the portable telephone according to this embodiment comprises a memory 2 that has recorded therein a reception history, a phone book (names and phone nos.) the user has registered, etc., an LCD display part 3 that displays phone numbers, time information, a residual capacity of battery, a reception field level, etc., an operation part 4 through that the user inputs a phone
30

number, etc., an LED 5 that turns "on" / "off" when reception has been made, a buzzer 6 that generates a reception sound when reception has been made, a vibrator 7 that makes a vibration when reception has been made, a wireless circuit 11 for performing wireless communication of a speech signal through an antenna 14, a speech-signal processing circuit 8 that demodulates a speech signal that has been transmitted over to the wireless circuit 11 to thereby output the demodulated signal to a receiver 9 and that modulates a speech signal that has been obtained through a microphone 10 to thereby output the modulated signal to the wireless circuit 11, a control circuit 1 for performing state detection or control of the memory 2, LCD display part 3, operation part 4, LED 5, buzzer 6, vibrator 7, speech-signal processing circuit 8, and wireless circuit 11, and a power source circuit 13 that is connected to a battery 12 and that is for the purpose of supplying a stable power source to the control circuit 1, memory 2, LED 5, buzzer 6, vibrator 7, speech-signal processing circuit 8, and wireless circuit 11. In the case no response to a reception is made and a history of this reception is recorded in the memory 2, the LED 5 turns "on" / "off", the vibrator 7 vibrates, or the buzzer 6 generates an alarming sound.

In the LCD display part 3, at the times when the telephone is in an ordinary standby, when reception is made, and when no response to a reception is made and a history of this reception is recorded in the memory 2, different information's are displayed, respectively.

Fig. 4 is a view illustrating information displayed on the LCD display part 3 illustrated in Fig. 2. Fig. 4(a) is information at the time when the telephone is in an ordinary standby; Fig. 4(b) is information at the time when reception is made; and Fig. 4(c) is information at the time when no response to a reception is made and a history of this reception is recorded.

In the LCD display part 3, at an ordinary standby such as after closure of the initial power source, as illustrated in Fig. 4(a), a calendar that shows the present time is displayed. When a call is received from a person who is registered in the phone book recorded
5 in the memory 2, as illustrated in Fig. 4(b) this person's name and phone number are displayed. Also, when no response to a reception is made and a history of this reception is recorded, as illustrated in Fig. 4(c) the present time is displayed along with the letters "someone called you".

10 The operation at the time of reception of the portable telephone that is constructed as stated above will now be explained with use of a flow chart. Here, the operation at the time of reception in a state where the present portable telephone has had an initial power source closed thereto and the LCD display part 3 has displayed thereon
15 the calendar (see Fig. 4(a)) at the ordinary standby will be explained.

Fig. 5 is a flow chart illustrating an example of the operation at the time of reception of the portable telephone illustrated in Fig. 2.

When a call is made from someone (step S1), in the control circuit
20 1, control is performed of causing a reception history to be recorded in the memory 2, causing the LED 5 to turn "on" / "off", causing the LCD display part 3 to display information (see Fig. 4(b)) at the time of reception, driving the buzzer 6 to generate a reception sound, or causing the vibrator 7 to vibrate. As a result of this, the reception
25 of the call is informed to the user and simultaneously the history of the reception is recorded in the memory 2 (step S2).

Next, it is determined whether the user has become aware of the informing of the reception and he has made a response to the reception (step S3). In the case it has been determined that the user's response
30 has been made, a phone talk between the user and the calling person

is performed (step S14). Then, when the phone talk is ended (step S15), the respective constituent elements provided within the portable telephone are operationally changed to their ordinary standby. On the other hand, the information indicating the ordinary standby (see Fig. 4(a)) is displayed on the LCD display part 3 (step S13).

Also, in the case in step S3 the user has not become aware of the informing of the reception and, because of no response made by him, the calling person has rung off and, resultantly, it has been determined that no response has been made by the user, the following results. Namely, on the LCD display part 3, there is displayed the information (see Fig. 4(c)) including therein the letters "someone called you" (step S4).

Subsequently, it is determined whether the reception history has been confirmed (step S5). In the case it has been determined that the user has confirmed the reception history by his prescribed operation, the information including therein the letters "someone called you" displayed on the LCD display part 3 is erased (step S12). Then, the flow proceeds to the processing of a step S13.

On the other hand, when it has been determined in step S5 that the user has not confirmed the reception history, it is determined whether the time length that has lapsed from the point in time of this determination is within a time length of T1 seconds (step S6). In the case it has been determined that that time length is so, the flow returns to the processing of the step S5.

Accordingly, in the case it has been determined in step S5 that the reception history has been confirmed within a time length of T1 seconds as counted from the point in time when the first determination of whether the reception history has been confirmed was made, the following results. Namely, the flow proceeds to the processings of steps S12 and S13, and then on the LCD display part 3 there is displayed

the standby window(see Fig. 4(a)).

In contrast, in the case it has been determined in step S5 that the reception history has not been confirmed even after a time length of T1 seconds as counted from the point in time when the first
5 determination of whether the reception history has been confirmed was made, the following results. Namely, the control circuit 1 causes the buzzer 6 to generate an alarming sound (step S7), whereby it is again determined whether the reception history has been confirmed (step S8).

10 In the case it has been determined in step S8 that the user has confirmed the reception history by his prescribed operation, the generation of the alarming sound by the buzzer 6 is stopped (step S11). Thereafter, the flow proceeds to the processing of the step 12.

15 On the other hand, when in step S8 it has been determined that the user has not confirmed the reception history, it is determined whether the time length that has elapsed from the point in time when a transfer was made from step S7 to step S8 is within a time length of T2 seconds (step S9). In the case that time length is within a
20 time length of T2 seconds, the flow returns to the processing of the step S7.

Accordingly, in the case it has been determined in step S8 that the reception history has been confirmed within a time length of T2 seconds as counted from the point in time when the first determination
25 of whether the reception history has been confirmed was made, the following results. Namely, the alarm is stopped in step S11 and then the flow proceeds to the processings of steps S12 and S13, and then on the LCD display part 3 there is displayed the standby window (see Fig. 4(a)).

30 In contrast, in the case it has been determined in step S8 that

the reception history has not been confirmed even after a time length of T2 seconds as counted from the point in time when the first determination was made, the following results. Namely, the generation of the alarming sound by the buzzer 6 is stopped (step S10). Then,
5 the flow again returns to the processing of the step S5.

As described above, in this embodiment, in the case no response to the forming of the reception is made and the reception history is recorded in the memory 2, the alarming sound is generated for a time length of T2 seconds in units of a time length of T1 seconds
10 until the reception history is confirmed.

As a result of this, because the user is urged to confirm the reception history, the fact that the reception has been made is informed earlier to the user.

It is to be noted that the above-described time lengths T1 and
15 T2 each are a given length of time. Therefore, each of the time lengths T1 and T2 may be one that is preset in the present portable telephone or may be one that the user arbitrarily sets.

Fig. 6 is a flow chart illustrating another example of the operation at the time of reception of the portable telephone illustrated
20 in Fig. 1.

In this example, it is arranged that only when the phone number the user has designated beforehand among the phone numbers registered in the phone book in the memory 2 has coincided with the phone number recorded in the reception history in the memory 2, the flow is
25 transferred to the processing of the alarm-sound generation in the steps from S6 to S11. To this end, with respect to the example illustrated in Fig. 5, a step S16 is added as the processing that is to be performed next to the step S5. It is to be noted that since other processings than that in step S16 are the same as the corresponding
30 pieces of processing in the example illustrated in Fig. 5, a detailed

explanation thereof is omitted.

In step S16, it is determined after a determination has been made in step S5 of that the reception history has not been confirmed whether the phone number designated beforehand coincides with the
5 phone number recorded in the reception history. And, only in the case the former coincides with the latter, the flow proceeds to the processings in steps S6 to S11, thereupon the processing of generating an alarm sound is performed.

Incidentally, in the case in step S16 it has been determined
10 that the phone number designated beforehand does not coincide with the phone number recorded in the reception history, the flow does not proceed to the processing of generating an alarm sound in steps S6 to S11. But, the flow returns to the processing in step S13, in which confirmation of the reception history is again performed.

15 As the contents of the processing in step S16, the following can be taken up as an example. Namely, only in the case the reception has notified its own phone number to the present user's telephone, the flow is transferred to the alarm-sound generation processing in steps S6 to S11. On the other hand, in the case the reception has
20 notified no phone number of its own, the flow is not transferred to the alarm-sound generation processing. Various kinds of settings are possible according to the user's choice. Thereby, it is possible to further enhance the phone's convenience of use.

In each of the examples illustrated in Figs. 5 and 6, an explanation
25 has been given of a construction wherein in the case no response is made to the informing of a reception and the history of this reception is recorded in the memory 2, the alarming sound of the buzzer 6 is generated until the history of the reception is confirmed. However, in the present invention, a construction of causing the vibrator 7
30 to vibrate, or a construction of causing the LED 5 to turn "on" /

"off", until the history of the reception is confirmed, may be adopted. Further, there may be adopted a construction wherein any two of the three operations in combination: lighting up of the LED 5, generation of the buzzer 6 sound, and vibration of the vibrator 7 are performed in combination. In addition, there may be adopted a construction having added thereto a function to permit the user to arbitrarily select combinations of these operations.

Also, in this embodiment, an explanation has been given of the construction of the collapsible type portable telephone. However, 10 as the construction of the portable telephone according to the present invention, it is not limited to a collapsible type but may be other construction than this collapsible type one.

As has been explained above, in the present telephone, it has been arranged that in the case no response to the informing of a reception 15 and the history of this reception is recorded, one or more of the generation of an alarming sound by the buzzer, the vibration made by the vibrator, and the lighting up of the LED are performed until the history of the reception is confirmed. Therefore, it is possible to urge the user to confirm the history of the reception and it is 20 thereby possible to inform the user earlier of the fact that the reception has been made.

Although the invention has been described with respect to specific embodiment for complete and clear disclosure, the appended claims are not to be thus limited but are to be construed as embodying 25 all modification and alternative constructions that may be occurred to one skilled in the art which fairly fall within the basic teaching here is set forth.

CLAIMS

1 1. A portable telephone in which the informing of a reception
2 is performed at the time of the reception by causing a buzzer to
3 generate its reception sound and simultaneously a history of the
4 reception is recorded in a memory, wherein

5 in the case no response to the informing of the reception
6 is made and the history of the reception is recorded in the memory,
7 the buzzer generates an alarming sound until the history of the
8 reception is confirmed.

1 2. A portable telephone according to claim 1, wherein
2 the buzzer generates its alarming sound for a prescribed time
3 length in units of a prescribed time length until the history of
4 the reception is confirmed.

1 3. A portable telephone according to claim 1 or 2, wherein
2 the memory records therein a telephone number that is
3 designated beforehand; and
4 the buzzer generates its alarming sound until the history
5 of the reception is confirmed only in the case a telephone number
6 of the reception coincides with the previously designated telephone
7 number that is recorded in the memory.

1 4. A portable telephone in which the informing of a reception
2 is performed at the time of the reception by causing an LED to turn
3 "on" / "off" and simultaneously a history of the reception is recorded
4 in a memory, wherein

5 in the case no response to the informing of the reception
6 is made and the history of the reception is recorded in the memory,
7 the LED turns "on" / "off" until the history of the reception is

8 confirmed.

1 5. A portable telephone according to claim 4, wherein
2 the LED turns "on" / "off" for a prescribed time length in
3 units of a prescribed time length until the history of the reception
4 is confirmed.

1 6. A portable telephone according to claim 4 or 5, wherein
2 the memory records therein the telephone number that is
3 designated beforehand; and
4 the LED turns "on" / "off" until the history of the reception
5 is confirmed only in the case the telephone number of the reception
6 coincides with the previously designated telephone number that is
7 recorded in the memory.

1 7. A portable telephone in which the informing of a reception
2 is performed at the time of the reception by causing a vibrator
3 to vibrate and simultaneously a history of the reception is recorded
4 in a memory, wherein
5 in the case no response to the informing of the reception
6 is made and the history of the reception is recorded in the memory,
7 the vibrator vibrates until the history of the reception is confirmed.

1 8. A portable telephone according to claim 7, wherein
2 the vibrator vibrates for a prescribed time length in units
3 of a prescribed time length until the history of the reception is
4 confirmed.

1 9. A portable telephone according to claim 7 or 8, wherein
2 the memory records therein a telephone number that is

3 designated beforehand; and

4 the vibrator vibrates until the history of the reception is
5 confirmed only in the case the telephone number of the reception
6 coincides with the previously designated telephone number that is
7 recorded in the memory.

1 10. A portable telephone in which the informing of a reception
2 is performed at the time of the reception by causing a buzzer to
3 generate its alarming sound and causing an LED to turn "on" / "off"
4 and simultaneously a history of the reception is recorded in a memory,
5 wherein

6 in the case no response to the informing of the reception
7 is made and the history of the reception is recorded in the memory,
8 the buzzer generates its alarming sound until the history of the
9 reception is confirmed; and

10 in the case no response to the informing of the reception
11 is made and the history of the reception is recorded in the memory,
12 the LED turns "on" / "off" until the history of the reception is
13 confirmed.

1 11. A portable telephone according to claim 10, wherein

2 the buzzer generates its alarming sound for a prescribed time
3 length in units of a prescribed time length until the history of
4 the reception is confirmed; and

5 the LED turns "on" / "off" for a prescribed time length in
6 units of a prescribed time length until the history of the reception
7 is confirmed.

1 12. A portable telephone according to claim 10 or 11, wherein

2 the memory records therein a telephone number that is
3 designated beforehand; and

4 the buzzer generates its alarming sound until the history
5 of the reception is confirmed only in the case the telephone number
6 of the reception coincides with the previously designated telephone
7 number that is recorded in the memory; and

8 the LED turns "on" / "off" until the history of the reception
9 is confirmed only in the case the telephone number of the reception
10 coincides with the previously designated telephone number that is
11 recorded in the memory.

1 13. A portable telephone in which the informing of a reception
2 is performed at the time of the reception by causing a buzzer to
3 generate its alarming sound and causing a vibrator to vibrate and
4 simultaneously a history of the reception is recorded in a memory,
5 wherein

6 in the case no response to the informing of the reception
7 is made and the history of the reception is recorded in the memory,
8 the buzzer generates its alarming sound until the history of the
9 reception is confirmed; and

10 in the case no response to the informing of the reception
11 is made and the history of the reception is recorded in the memory,
12 the vibrator vibrates until the history of the reception is confirmed.

1 14. A portable telephone according to claim 13, wherein
2 the buzzer generates its alarming sound for a prescribed time
3 length in units of a prescribed time length until the history of
4 the reception is confirmed; and

5 the vibrator for a prescribed time length in units of a

6 prescribed time length until the history of the reception is
7 confirmed.

1 15. A portable telephone according to claim 13 or 14, wherein
2 the memory records therein a telephone number that is
3 designated beforehand; and

4 the buzzer generates its alarming sound until the history
5 of the reception is confirmed only in the case the telephone number
6 of the reception coincides with the previously designated telephone
7 number that is recorded in the memory; and

8 the vibrator vibrates until the history of the reception is
9 confirmed only in the case the telephone number of the reception
10 coincides with the previously designated telephone number that is
11 recorded in the memory.

1 16. A portable telephone in which the informing of a reception
2 is performed at the time of the reception by causing an LED to turn
3 "on" / "off" and causing a vibrator to vibrate and simultaneously
4 a history of the reception is recorded in a memory, wherein

5 in the case no response to the informing of the reception
6 is made and the history of the reception is recorded in the memory,
7 the LED turns "on" / "off" until the history of the reception is
8 confirmed; and

9 in the case no response to the informing of the reception
10 is made and the history of the reception is recorded in the memory,
11 the vibrator vibrates until the history of the reception is confirmed.

1 17. A portable telephone according to claim 16, wherein
2 the LED turns "on" / "off" for a prescribed time length in

3 units of a prescribed time length until the history of the reception
4 is confirmed; and

5 the vibrator vibrates for a prescribed time length in units
6 of a prescribed time length until the history of the reception is
7 confirmed.

1 18. A portable telephone according to claim 16 or 17, wherein
2 the memory records therein a telephone number that is
3 designated beforehand; and

4 the LED turns "on" / "off" until the history of the reception
5 is confirmed only in the case the telephone number of the reception
6 coincides with the previously designated telephone number that is
7 recorded in the memory; and

8 the vibrator vibrates until the history of the reception is
9 confirmed only in the case the telephone number of the reception
10 coincides with the previously designated telephone number that is
11 recorded in the memory.

1 19. A portable telephone according to claim 16, wherein
2 the generation of the reception sound is made at the time
3 of the reception and, in the case no response to the informing of
4 the reception is made and the history of the reception is recorded
5 in the memory, the buzzer generates its alarming sound until the
6 history of the reception is confirmed.

1 20. A portable telephone according to claim 19, wherein
2 the buzzer generates its alarming sound for a prescribed time
3 length in units of a prescribed time length until the history of
4 the reception is confirmed;

5 the LED turns "on" / "off" for a prescribed time length in
6 units of a prescribed time length until the history of the reception
7 is confirmed; and

8 the vibrator vibrates for a prescribed time length in units
9 of a prescribed time length until the history of the reception is
10 confirmed.

1 21. A portable telephone according to claim 19 or 20, wherein
2 the memory records therein a telephone number that is
3 designated beforehand;

4 the buzzer generates its alarming sound until the history
5 of the reception is confirmed only in the case the telephone number
6 of the reception coincides with the previously designated telephone
7 number that is recorded in the memory;

8 the LED turns "on" / "off" until the history of the reception
9 is confirmed only in the case the telephone number of the reception
10 coincides with the previously designated telephone number that is
11 recorded in the memory; and

12 the vibrator vibrates until the history of the reception is
13 confirmed only in the case the telephone number of the reception
14 coincides with the previously designated telephone number that is
15 recorded in the memory.

22. A portable telephone substantially as herein described with reference to Fig. 2 et seq. of the drawings.

23. A method of operating a portable telephone, comprising the steps of:

5 informing the user of reception of a call at the time of reception;

 recording a record of the reception in a memory; and

 if no response has been made to the informing step, and
10 if the record of the reception has been recorded, generating an alarm to the user.

24. A method of operating a portable telephone, substantially as herein described with reference to Fig. 2 et seq. of the drawings.



INVESTOR IN PEOPLE

Application No: GB 0104709.1
Claims searched: 1-24

Examiner: Robert Shorthouse
Date of search: 3 December 2001

Patents Act 1977 Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK Cl (Ed.S): H4L (LERA, LERX, LECCP, LECCX), H4K (KHBC), G4G (HRCU)

Int Cl (Ed.7): H04Q 7/32, H04M 1/725, 11/04

Other: Online: WPI, EPODOC, JAPIO, INSPEC

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
A	GB 2333205 A (NEC) See abstract	-
X	GB 2284693 A (NEC) See page 3 paragraph 2	1, 2, 4, 5, 7, 8, 10, 11, 13, 14, 16, 17, 19, 20, 23
A	GB 2253541 A (TECHNOPHONE) See abstract	-

X Document indicating lack of novelty or inventive step
Y Document indicating lack of inventive step if combined with one or more other documents of same category.

& Member of the same patent family

A Document indicating technological background and/or state of the art.
P Document published on or after the declared priority date but before the filing date of this invention.
E Patent document published on or after, but with priority date earlier than, the filing date of this application.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

This Page Blank (uspto)